



J&S Matus Motorsports, Inc. DBA: The Texas Mile

Rules, Regulations & Technical Specifications (RRTS)

© 2003, 2004, 2005, 2006, 2007, 2008, 2009, 2010, 2011, 2012,2013, 2014, 2015, 2016,2017,
2018, 2019,2020, 2021,2022

2022 Edition ©

THIS BOOK IS AN OFFICIAL PUBLICATION OF J&S MATUS MOTORSPORTS, INC. DBA THE TEXAS MILE

THE CONTENTS OF THIS BOOK ARE THE SOLE PROPERTY OF J&S MATUS MOTORSPORTS, INC. DBA
THE TEXAS MILE. NO PORTION OF THIS BOOK MAY BE REPRODUCED IN ANY MANNER,
ELECTRONICALLY TRANSMITTED, POSTED ON THE INTERNET, RECORDED BY ANY MEANS, OR STORED
ON ANY MAGNETIC / ELECTROMAGNETIC STORAGE SYSTEM(S) WITHOUT THE EXPRESS WRITTEN
CONSENT FROM THE CEO or COO OF J&S MATUS MOTORSPORTS, INC DBA THE TEXAS MILE
NOTE- THE VERSION POSTED ON THE TEXAS MILE OR U.S. MILE WEBSITE MAY BE PRINTED FOR
PERSONAL USE.

J&S Matus Motorsports, Inc. DBA The Texas Mile

www.texasmile.net

info@texasmile.net

Phone: +1 (281) 303-1844

The U.S. Mile Top Speed Racing events which hosts The Texas Mile is a competitive motor sports event, the conduct of which is governed by The U.S. Mile/Texas Mile Staff in accordance with its Rules, Regulations & Technical Specifications. These Rules, Regulations & Technical Specifications may be amended from time to time, along with any special rules, regulations & technical specifications that may be issued by The U.S. Mile/The Texas Mile for a specific event and/or any applicable agreement to which The U.S. Mile/The Texas Mile is a party.

All cars, motorcycles, drivers, and riders, and entrants will be subject to The U.S. Mile/The Texas Mile Rules, Regulations & Technical Specifications, specifically the Technical Requirements, Required Safety Equipment, Vehicle Safety Inspection and General Competition Vehicle Rules. These sections cover rules for safety equipment, including but not limited to full roll cages, safety belts, fire extinguishers, as well as appearance and other items. All drivers/riders must have a current Texas Mile or U.S. Mile competition license.

In the event there is any difference between this version of Rules, Regulations & Technical Specifications and the supplement version you receive in your Driver Packet, the version in your Driver Packet will take precedence. The U.S. Mile/The Texas Mile Staff reserves the right to amend or change the rules at any time in the interests of safety. Waivers and exceptions to these requirements may be granted on a case-by-case basis by the Race Director, Chief of Tech, or Owners of the The U.S. Mile/Texas Mile.

These Rules, Regulations & Technical Specifications are a guide toward a universal competition goal, and interpretation will be made by the The U.S. Mile/Texas Mile Staff. Any situation not included or not specifically covered in the Rules, Regulations & Technical Specifications will be acted upon by U.S. Mile/Texas Mile Staff and their decisions will be final and non-negotiable.

The U.S. Mile/The Texas Mile Staff will perform an inspection of the required safety equipment for an assurance of its presence on the vehicle. This inspection is primarily a courtesy to the entrant and in no way expresses or implies a warranty of safety. Responsibility for the safe installation and use of this safety equipment is the sole responsibility of the entrant.

ALL PARTICIPANTS MUST COMPLETE THE TECHNICAL INSPECTION PROCEDURE PRIOR TO COMPETITION.

The U.S. Mile/The Texas Mile Staff reminds you that all motor sports are dangerous and the safety of yourself and your race vehicle is solely your responsibility. Please pay particular attention to the minimum safety equipment required in the following Rules, Regulations & Technical Specifications of The U.S. Mile/Texas Mile.

Driver/Rider Disclaimer: Conformance to these regulations is the driver's/rider's responsibility. There will be NO EXCEPTIONS to these rules and regulations and The U.S. Mile/The Texas Mile WILL NOT give refunds nor transfer your entry to any future events to participants who do not meet the SAFETY REQUIREMENTS.

2022 Texas Mile

Rules, Regulations, & Technical Specifications

Table of Contents

1.0	Acceptance.....	12
2.0	Competition & Publicity Waivers.....	13
3.0	Participant Terms and Conditions.....	13
4.0	Automobiles Required Safety Equipment (under 199 mph)	14
4.1	TIRES.....	14
4.1.1	Biased Ply Tires.....	14
4.1.2	Tire Rating.....	14
4.1.3	Recommendations.....	14
4.1.4	Slick Tires.....	14
4.1.5	Road Race “W Rating”	15
4.1.6	Tires dated 7 years or older.....	15
4.2	FIRE EXTINGUISHER.....	15
4.3	HELMET.....	15
4.3.1	Shatterproof Eyeglasses	15
4.3.2	Open Cockpit Specifications.....	15
4.3.3	Padded Neck Collar and/or Helmet Restraint.....	15
4.3.4	Display SNELL SA2015 or SA2020	15
4.4	SEAT BELTS/DRIVER RESTRAINTS.....	16
4.4.1	Open Cockpit Arm Restraints and Harness.....	16
4.5	CLOTHING.....	16

4.6	ROLL BAR/ ROLL CAGE/ CONVERTIBLE TOPS/ OPEN COCKPIT.....	16
4.7	BRAKES.....	16
4.8	VEHICLE COMPONENTS IN GOOD OPERATING CONDITION.....	17
5.0	Automobiles Required Safety Equipment (At 199 mph to 215 mph).....	17
5.1	TIRES.....	17
5.1.1	Biased Ply Tires.....	17
5.1.2	Tires Ratings.....	18
5.1.3	Tire Recommendations.....	18
5.1.4	Slick Tires.....	18
5.1.5	Road Race “W Rating”	18
5.1.6	Tires dated 7 years or older.....	18
5.2	FIRE EXTINGUISHER.....	18
5.3	HELMET.....	18
5.3.1	Display SNELL SA2015 or SA2020.....	18
5.3.2	Padded Neck Collar and/or Helmet Restraint.....	18
5.3.3	Full Faced Helmets/Face Shield.....	18
5.4	SEAT BELTS/SAFETY HARNESS.....	19
5.4.1	Seat Belt Specifications.....	19
5.4.2	A Five-Point System.....	19
5.4.3	A Six-Point System.....	19,20
5.4.4	A Seven-Point System.....	20
5.4.5	Strap Material.....	20
5.4.6	Mounting Hardware Specifications.....	20
5.4.7	Shoulder Harness Specifications.....	20

5.4.8	Shoulder Strap Specifications.....	20
5.4.9	Driver’s Responsibility of Seatbelts.....	20
5.4.10	Driver Responsibility in Case of Driving Incident.....	21
5.5	CLOTHING.....	21
5.6	ROLL BAR/CAGE.....	21
5.6.1	Cage Permanence/Removability Specifications.....	21
5.6.2	Cage Padding.....	22
5.7	BRAKES.....	22
5.8	VEHICLE COMPONENTS IN GOOD OPERATING CONDITION.....	22
6.0	Automobile Required Safety Equipment (215-230 mph)	23
6.1	TIRES.....	23
6.1.1	Biased Ply Tires.....	23
6.1.2	Tire Rating.....	23
6.1.3	Tire Recommendations.....	24
6.1.4	Slick Tires.....	24
6.1.5	Road Race “W Rating”	24
6.1.6	Tires dated 7 years or older.....	24
6.2	DRIVERS SEAT SAFETY REQUIREMENTS.....	24
6.3	FIRE EXTINGUISHER.....	24
6.4	HELMET.....	24
6.4.1	Display SNELL SA2015 or SA2020	24
6.4.2	Full Faced Helmets/Face Shield.....	25
6.5	SEAT BELTS/SAFETY HARNESS/RESTRAINTS/HANS.....	25

6.5.1	Seat Belt Specifications.....	25
6.5.2	A Five-Point System.....	25
6.5.3	A Six-Point System.....	25
6.5.4	A Seven-Point System.....	25
6.5.5	Strap Material	26
6.5.6	Mounting Hardware.....	26
6.5.7	Driver’s Seat Requirement.....	26
6.5.8	Shoulder Strap Specifications.....	26
6.5.9	Driver’s Responsibility of Seatbelts.....	26
6.5.10	Driver Responsibility in Case of Driving Incident.....	26
6.6	CLOTHING.....	26
6.7	ROLL BAR/CAGE REQUIREMENTS.....	27
6.7.1	Bar stock material minimums.....	27
6.7.2	Roll cage construction requirements.....	27
6.7.3	Cage Padding.....	27
6.8	BRAKES.....	28
6.9	VEHICLE COMPONENTS IN GOOD OPERATING CONDITION.....	28
7.0	Automobile Required Safety Equipment (230+ mph).....	28
7.1	TIRES.....	28
7.1.1	Biased Ply Tires.....	29
7.1.2	Tire Rating.....	29
7.1.3	Tire Recommendations.....	29
7.1.4	Slick Tires	29
7.1.5	Road Race “W Rating”	29

7.1.6	Tires dated 7 years or older.....	29
7.2	DRIVERS SEAT SAFETY REQUIREMENTS.....	29
7.3	FIRE EXTINGUISHER REQUIREMENTS.....	29
7.4	HELMET.....	30
7.4.1	Display of SNELL SA2015 or SA2020.....	30
7.4.2	Full Faced Helmets/Face Shield.....	30
7.5	SEAT BELTS/SAFETY HARNESS/RESTRAINTS/HANS REQUIREMENTS.....	30
7.5.1	Seat Belt Specifications.....	30
7.5.2	A Five-Point System.....	30
7.5.3	A Six-Point System.....	31
7.5.4	A Seven-Point System.....	31
7.5.5	Strap Material	31
7.5.6	Mounting Hardware.....	31
7.5.7	Shoulder Strap Specifications.....	31
7.5.8	Driver’s Responsibility of Seatbelts.....	31
7.5.9	Driver Responsibility in Case of Driving Incident.....	31
7.6	CLOTHING.....	32
7.7	ROLL CAGE REQUIREMENTS.....	32
7.7.1	Bar stock material minimums.....	32
7.7.2	Roll cage construction requirements.....	32
7.7.3	Cage Padding.....	32,33
7.8	BRAKES.....	33
7.9	VEHICLE COMPONENTS IN GOOD OPERATING CONDITION.....	33

8.0	Automobile Classification Rules.....	33
8.1	STREET LEGAL.....	33
8.2	NOT STREET LEGAL.....	33
8.3	EXHIBITION VEHICLE.....	33
8.4	QUESTIONS YOU MUST ANSWER.....	33
8.4.1	Body Style.....	33
8.4.2	Speed Range.....	33
8.4.3	Engine Induction.....	33
8.4.4	Engine.....	33
8.4.5	Cubic Inch / Liter Equiv. Range.....	33
8.4.6	Fuel.....	33
8.4.7	Nitrous.....	34
8.4.8	Methanol Injected.....	34
8.4.9	Drive Line.....	34
9.0	Motorcycles – Required Safety Equipment.....	35
9.1	ENGINE KILL SWITCH.....	35
9.2	TIRES.....	35
9.3	SAFETY-WIRED ITEMS.....	35
9.3.1	Front Axels.....	35
9.3.2	Oil Drain Plugs.....	35
9.3.3	Drive Chains.....	35
9.4	BREATHER HOSES.....	35
9.5	CLOTHING.....	35,36
9.6	HELMET.....	36
9.6.1	Display of SNELL SA2015 or SA2020.....	36
9.6.2	Visor tear-offs.....	36

9.6.3	Hydration Devices.....	36
9.7	STEERING DAMPER.....	36
9.8	BRAKES.....	36
10.0	Motorcycles – Classification Rules.....	37
10.1	INLINE MOTOR/FACTORY STOCK.....	37
10.2	INLINE MOTOR/MODIFIED.....	37
10.3	INLINE MOTOR/UNLIMITED.....	37
10.4	V TWIN MOTOR/FACTORY STOCK.....	37
10.5	V TWIN MOTOR /MODIFIED.....	37
10.6	V TWIN MOTOR /UNLIMITED.....	37
10.7	EXHIBITION MOTORCYCLE CLASS.....	37
10.8	CLASSIFICATION DEFINITIONS.....	37
10.8.1	Factory Stock.....	37
10.8.2	Modified.....	37
10.8.3	Unlimited.....	38
10.9	QUESTIONS YOU MUST ANSWER.....	38
10.9.1	Body Style.....	38
10.9.2	Manufacture Origin.....	38
10.9.3	Engine Induction.....	38
10.9.4	Engine.....	38
10.9.5	Cubic Centimeters.....	38
10.9.6	Fuel.....	38
10.9.7	Nitrous.....	38
10.9.8	Methanol Injected.....	38
10.9.9	Inches over stock length.....	38
11.0	Land Speed Racer Classification.....	39

11.1	LAND SPEED RACING AUTOMOBILE.....	39
11.2	LAND SPEED RACING MOTORCYCLE.....	39
11.3	QUESTIONS YOU MUST ANSWER: LSR AUTOMOBILE.....	39
	11.3.1 Body Style.....	39
	11.3.2 Speed Range.....	39
	11.3.3 Engine Induction.....	39
	11.3.4 Engine.....	39
	11.3.5 Cubic Inch / Liter Equiv. Range.....	39
	11.3.6 Fuel.....	39
	11.3.7 Nitrous.....	39
	11.3.8 Methanol Injected.....	39
	11.3.9 Drive Line.....	39
11.4	QUESTIONS YOU MUST ANSWER: LSR MOTORCYCLES.....	39
	11.4.1 Body Style.....	39
	11.4.2 Manufacture Origin.....	39
	11.4.3 Engine Induction.....	40
	11.4.5 Engine.....	40
	11.4.6 Cubic Centimeters.....	40
	11.4.7 Fuel.....	40
	11.4.8 Nitrous.....	40
	11.4.9 Methanol Injected.....	40
	11.4.10 Inches over stock length.....	40
11.5	BODY STYLE DEFINITIONS FOR MOTORCYCLES.....	40
	11.5.1 Sport bike or Superbike.....	40
	11.5.2 Sport-Touring Bikes.....	40
	11.5.3 Classic/Cruiser/Touring Motorcycles.....	40

11.5.4 Chopper/Bobber/Café/Brat/Scrambler.....	40
11.5.5 Enduro/Dual-Sport Motorcycles.....	40
11.5.6 Other.....	41
12.0 Competitor Licensing.....	41
12.1 CLASS C LICENSE.....	41
12.2 CLASS B LICENSE.....	41
12.3 CLASS A LICENSE.....	41,42
12.4 CLASS AA LICENSE.....	42
12.5 FINAL SAY.....	42
Contact Us.....	43

1.0 Acceptance

All persons or groups making an official entry into the Texas Mile or U.S. Mile events are to be knowledgeable of the rules, regulations and technical specifications (RRTS). **All participants understand that vehicle passengers are NOT allowed in the vehicle while making a pass down the track.** An entrant's participation in the event and submission of the on-line registration and/or mailed official entry form shall constitute an acknowledgement and acceptance of the RRTS. The decision of the organizers in their interpretation and enforcement of the RRTS are final.

Prior safety and technical approval from other racing or land speed events is not proof or waiver allowing exemption from any automobile or driver safety specification set forth in RRTS. Individuals in cars attempting runs over 199 mph without the proper equipment or license may be dismissed from the event with no refund and/or fined, and potentially banned from all future Texas Mile and U.S. Mile events.

Vehicles must remain as is once the vehicle has passed and been cleared through Technical Inspection. Any deviation from the vehicles approved Technical Inspection without prior approval from the Tech Director or Race Director will be disallowed from the remainder of the event without refund. This includes but is not limited to a change in tires, seat, or restraints.

The vehicle tech Limit is the maximum speed that The Texas Mile or U.S. Mile will allow a given vehicle allow based on the criteria listed in the RRTS. The limit is determined by the technical specifications that are required for each level. The "Technical Speed Limit" for each vehicle will be assigned at Tech Inspection and a different tech sticker will be given for each level.

In addition to the Tech Limit for the vehicle, there is also a License program based on each entrant's experience level. This is the highest speed that The Texas Mile and U.S. Mile will allow a given entrant to achieve. A competitor's speed license may be raised during an event if the competitor follows the procedures detailed in the licensing section.

2.0 Competition & Publicity Waivers

All persons admitted to the pre-grid, race-grid and/or other restricted areas of Texas Mile/U.S. Mile Staff sanctioned events must obey all of the Rules, Regulations & Technical Specifications set forth by Texas Mile/U.S. Mile Staff. Each person admitted must complete and sign all releases of liability requested by Texas Mile/U.S. Mile Staff.

All entrants empower Texas Mile/U.S. Mile to represent them in assigning rights for reproduction of sanctioned events by electronic, broadcast and/or print media and automatically assign rights to utilize their name, facsimile, etc., in media related materials and/or advertising and promotion of sanctioned events.

3.0 Participant – Terms and Conditions

All participants agree to accept announcements pertaining to Texas Mile/ U.S. Mile related activities or offers via mail or email. All Texas Mile/U.S. Mile participants agree to assign any and all video and still photo rights to The Texas Mile or The U.S. Mile for any purposes deemed appropriate by The Texas Mile and The U.S. Mile Staff.

The Texas Mile and The U.S. Mile own or license all copyright rights in images, video, audio, graphics, photographs or any other content related to The Texas Mile and The U.S. Mile to the full extent provided under the copyright laws of the United States. Except as expressly provided in any written agreement with The Texas Mile/ The U.S. Mile, you are prohibited from copying, reproducing, modifying, distributing, displaying or transmitting any content related to The Texas Mile or The U.S. Mile. You may use images, video, audio, graphics, and photographs for your own individual non-commercial and informational purposes only.

4.0 Automobiles - Required Safety Equipment (under 199 mph).

Prior safety and technical approval from other racing or land speed events is not proof or waiver allowing exemption from any automobile or driver safety specification set forth in these rules. The following safety equipment is required to be used for all automobiles running up to 199 mph. All Monocoque Chassis are given a 10 MPH additional safety bump at all speed requirements

****DOT TIRES MUST HAVE AN "A" TEMPERATURE RATING OR BETTER****

4.1 TIRES: DOT tires must have an "A" temperature rating or better. DOT approved or competition road race (slick) tires in good condition are required to be used. The tire speed rating must exceed the speed that the driver is attempting to achieve.

4.1.1 Tires of any construction for use in land speed competition on nonpaved surfaces, tires designated for use in drag racing and biased ply tires designed for highway or off-road use, are strictly forbidden.

4.1.2 It is REQUIRED that all tires must have a Temperature rating of "A" or greater than the original (OEM) manufacturer's requirement. Load ratings and speed ratings below OEM requirements will not be allowed. **W-up to 168MPH, Y-up to 186MPH, [Y] "Bracket" (Y) 186MPH+**

4.1.3 It is RECOMMENDED that the participant make use of tires with a speed, temperature and load rating exceeding the original OEM specification for that particular vehicle.

4.1.4 Any Slick tire (non DOT stamped) must be approved by the Chief of Tech at least 30 days prior to the event. **Drag Racing Slicks Are NOT allowed**

4.1.5 **Road Race** compounds carrying a speed rating of “W” may be run in excess of its stated speed rating at The Texas Mile and US Mile Events.

4.1.6 Tires with a date code **7 years** or older will not be allowed.

4.2 FIRE EXTINGUISHER: A fire extinguisher is not required for cars under 199 mph. If a fire extinguisher or fire system is installed, it needs to be properly mounted/installed according to manufacturer recommendations.

4.3 HELMET: Helmets must carry a SNELL SA-Rating (Special Application) **2015** or newer certification (**SA2015 or SA2020**). **Note: Helmets carrying only a DOT Certification or an M-Rating (Motorcycle) helmets are forbidden for use in an automobile in any class at any speed. All helmets must be in sound condition including shell liner and strap.**

4.3.1 Shatterproof eyeglasses will be the minimum standard if helmet is not full face with eye protection/shield.

4.3.2 If an automobile is an open cockpit, **a full face SA2015 or newer SA2020 helmet** will be required.

4.3.3 A padded neck collar or a HANS device is recommended but not required.

4.3.4 Helmets unable to display SNELL SA2015 or SA2020 stickers (located on the inner shell of the helmet) will not be approved for use.

4.4 SEAT BELTS/DRIVER RESTRAINTS: Correctly installed factory seat belts, OEM or better, is the minimum standard required to be used by each driver. Restraints must be in “as new” condition. Lap belts, OEM or otherwise, used without any shoulder restraints are not permitted. A racing harness may be used provided that it is in good condition and mounted per the manufacturer’s recommendations, otherwise you will be asked to use your factory seat belt. Aftermarket DOT-certified belt sets, installed to the manufacturer’s specifications may be allowed. Proof of DOT certification and proper installation is the driver’s responsibility. Vintage cars (25 years or older) must have new belts or harnesses. All aftermarket restraints must be manufactured within 10 years of the current event.

4.4.1 Open cockpit cars require the use of driver arm restraints and a minimum 5pt harness with SFI approved containment seat meeting SFI 39.2. See section 5.4.1 for belt/harness requirements.

4.5 CLOTHING: SFI approved driving gloves are REQUIRED. Synthetic mechanics/work gloves are not considered appropriate glove wear. Non-synthetic fabric clothing (cotton, wool, leather etc.), covering torso, arms and legs, plus shoes without holes are the minimum standard required to be worn by the driver of the vehicle. Open-toed shoes, shorts, or short sleeve shirts may not be worn. An **SFI 3.2A/1** (or better) Driver's suit and SFI 3.3/1 or better Driver's Accessories (shoes, balaclava, gloves, underwear) are highly recommended but not required.

4.6 ROLL BAR/ ROLL CAGE/ CONVERTIBLE TOPS/OPEN COCKPIT: A competition approved Roll Bar for an open vehicle (convertible or open cockpit) is mandatory unless your vehicle is equipped with a factory rollover protection system. Factory A pillars are not considered factory roll over protection. (Please contact The Texas Mile or U.S. Mile Chief of Tech regarding approval for convertibles). Convertibles must run with the top in the up position.
Chief of Tech Contact: Kevin Mixon, 832-658-1236

For all other applications, a 4-point Roll Bar is recommended at a minimum but not required.

4.7 BRAKES: All vehicles must have working front and rear brakes.

4.8 VEHICLE COMPONENTS IN GOOD OPERATING CONDITION: Please make sure your vehicle is in good working condition. No leaks from the vehicle or loose items within the vehicle are allowed. Floor mats need to be removed. Ice may be used for intercoolers. Fresh fluids such as lubricants and coolants throughout the vehicle are recommended. See the tech sheet for further details.

5.0 Automobiles – Required Safety Equipment (At 199 mph to 215mph)

Prior safety and technical approval from other racing or land speed events is not proof or waiver allowing exemption from any automobile or driver safety specification set forth in these rules. The following safety equipment is required to be used for all automobiles running at 199 mph to 215 mph, and highly recommended for all other vehicles at lesser speeds. You must submit a safety equipment check-list to the Texas Mile or the U.S. Mile and gain approval to enter a vehicle attempting speeds over 199 mph. All Monocoque Chassis are given a 10 MPH additional safety bump at all speed requirements

****DOT TIRES MUST HAVE AN “A” TEMPERATURE RATING OR BETTER****

5.1 TIRES: DOT tires must have an “A” temperature rating or better. DOT-approved or competition road race (slick) tires in good condition are required for any vehicle. The tires speed rating must exceed the speed that the driver is attempting to achieve. All tires on the vehicle must be **Bracket (Y) Rated** or a competition Road Race tire rated for speeds greater than 190 MPH.

W-up to 168MPH, Y-up to 186MPH, [Y] “Bracket” (Y) 186MPH+

Example: 315-35-R18 (Y)

- 5.1.1** Tires of any construction for use in land speed competition on nonpaved surfaces, tires designated for use in drag racing and biased ply tires designed for highway or off-road use, are strictly forbidden.
- 5.1.2** All tires must have a Temperature rating of “A” (or greater) and Speed Rating (Y). Load ratings below OEM requirements will not be allowed.
- 5.1.3** It is HIGHLY RECOMMENDED that the participant use tires with a speed, temperature and load rating exceeding the rules set forth in this section.
- 5.1.4** Any Slick tire (non DOT stamped) must be approved by Chief of Tech at least 30 days prior to the event. Drag racing slicks are NOT allowed.
- 5.1.5** **Road Race** compounds carrying a speed rating of “W” may be run in excess of its stated speed rating at The Texas Mile and US Mile Events.
- 5.1.6** Tires with a date code 7 years or older will not be allowed.
- 5.2** **FIRE EXTINGUISHER:** A 2lb minimum, automotive BC handheld fire extinguisher must be installed, with a secure quick release-mounting bracket preferably made of metal, mounted within easy reach of the Driver while normally seated, belts fastened, & steering wheel in place. A fire system is recommended but not required.
- 5.3** **HELMET:** Helmets must carry a SNELL SA-Rating (Special Application) **2015** or newer certification (**SA2015 or SA2020**). **Note: Helmets carrying only a DOT Certification as well as M-Rating (Motorcycle) helmets are forbidden for use in an automobile in any class at any speed. All helmets must be in sound condition including shell liner and strap.**

5.3.1 Helmets unable to display **SNELL SA2015** or newer stickers (located on the inside shell of the helmet) will not be approved for use.

5.3.2 A padded neck collar or HANS device is recommended but NOT required

5.3.3 Helmets must be full faced and have the face shield installed.

5.4 SEAT BELTS/SAFETY HARNESS: All vehicles must have a five-, six-, or seven-point seat belt system/safety harness. **A Race Seat or factory style Recaro seats with shoulder belt guide holes (This is not the gap between the head restraint and top of the seat.)** A hole for the submarine strap is recommended. Alternative submarine strap mounting bars are approved. Arm restraints are required in open cockpit cars and cars with open T-tops, open Targa tops, missing moon/sun roofs, or glass moon/sun roofs.

5.4.1 All belts should meet at least one of the following:

- A.** SFI Specification 16.1 or 16.5 and shall bear a dated label of no more than five (5) years old. At least one date label is required on belt sets.
- B.** A restraint system meeting FIA spec #8853/1985, 8853/98, or D-###.T/98, including amendment 1/92 may be used. FIA certified belts have a label that shows an expiration date. The belts cannot be used past December 31st of the year shown on the label. At least one date label is required on belt sets. Belts cannot be over 5 years old by the date shown on the label.

- 5.4.2** A five-point system consists of: a three (3) inch lap belt, two shoulder belts that are either two (2) inch (*for use with HANS only*) or three (3) inches wide, and a two (2) inch anti-submarine strap.
- 5.4.3** A six-point system is recommended for cars where the driver is seated in an upright (to thirty (30) degrees) or a semi-reclining position. It consists of two (2) anti-submarine belts in addition to lap and shoulder belts. Note: Current FIA-approved belt sets with two (2) inch lap belts are acceptable with the six-point system.
- 5.4.4** A seven-point system is recommended for seats with more than thirty (30) degrees of incline. Note: Current FIA Approved belt sets with two (2) inch lap belts are acceptable with the seven (7) point system.
- 5.4.5** The material of all straps should be nylon or polyester, and in new or perfect condition. The buckles must be metal quick release. There should be a common release for all belts. [Note: Certain Momo-brand belts were recalled by the manufacturer. These are NOT suitable.]
- 5.4.6** All mounting hardware must be SAE grade five (5) or better. Large diameter mounting washers should be used to spread the load. Bolting through floor panels etc. is not acceptable without required washers. Please consult an experienced race car preparation shop for mounting your safety harness.
- 5.4.7** The seat must be equipped with proper shoulder harness holes or the cage/roll bar needs to have a guide to prevent the shoulder harnesses from falling to the sides. The guide bar, if used, must not present a sharp edge to the belts. It must provide as much area of support as possible to distribute the load.
- 5.4.8** Only separate shoulder straps are permitted. "H" type belts are allowed. "Y" type belts are not allowed. Each shoulder strap must have an independent mounting point.

5.4.9 All drivers will take care to ensure that their belts are properly worn, adjusted, and latched. “Cam-lock” type belts can be subject to inadvertent release, should the driver fail to ensure that they are properly latched.

5.4.10 Any driver involved in a high impact crash shall send all of their safety belts back to the manufacturer for inspection, re-webbing if necessary, and re-certification before they may be used again. Proof of re-certification is the driver’s responsibility.

5.5 CLOTHING: An SFI 3.2A/1 (or better) Driver's suit and SFI 3.3 Driver's Accessories (gloves, shoes, underwear, socks, and balaclava (if you have facial hair) are required.

5.6 ROLL BAR/CAGE: All cars that are attempting speeds at or over 199 mph are required to have a **four-point** roll bar at minimum. A six-point or eight-point cage is highly recommended. The material and minimums are as follows:

FOR DOM: under 2500lbs: 1.50"x 0.095"
 2501-3000lbs: 1.50"x 0.120" or 1.75" x 0.095"
 over 3001lbs: 1.75"x 0.120"

FOR Alloy (CM): under 1500lbs: 1.375"x 0.095"
 1501-2500lbs: 1.50"x 0.095"
 2501-3000lbs: 1.50"x 0.120" or 1.75" x 0.095"
 3001+lbs: 1.75" x 0.120"

5.6.1 The cage may be removable or may be permanently welded, or any combination thereof, providing that all aspects of the cage meet these rules.

5.6.2 All roll cage surfaces that may come in contact with the driver should be padded with high-density padding such as Ethafoam or Ensolite. It is recommended that the padding meeting SFI specification 45.1 be used.

NOTE: Any individual wishing to enter a vehicle which deviates from the rules listed above must contact the Chief of Tech 30 days prior to the event for approval.

5.8 BRAKES: All vehicles must have working front and rear brakes.

5.9 VEHICLE COMPONENTS IN GOOD OPERATING CONDITION: Please make sure your vehicle is in good working condition. No leaks from the vehicle or loose items within the vehicle are allowed. Floor mats need to be removed. Ice may be used for intercoolers. Fresh fluids such as lubricants and coolants throughout the vehicle are recommended.

6.0 Automobile - Required Safety Equipment 215-230 mph

Prior safety and technical approval from other racing or land speed events is not proof or waiver allowing exemption from any automobile or driver safety specification set forth in these rules. The following safety equipment is required to be used for all automobiles running at 215 mph to 230 mph, and highly recommended for all other vehicles. You must submit a safety equipment check-list to the Texas Mile or the U.S. Mile and gain approval to enter a vehicle attempting speeds over 199 mph. All Monocoque Chassis are given a 10 MPH additional safety bump at all speed requirements

ATTENTION: DOT TIRES MUST HAVE AN "A" TEMPERATURE RATING OR BETTER.

****DOT TIRES MUST HAVE AN "A" TEMPERATURE RATING OR BETTER****

- 6.1 **TIRES: TIRES MUST HAVE A TEMPERATURE RATING OF "A" OR BETTER.** DOT-approved or competition road race (slick) tires in good condition are required to be used. *The tire speed rating must exceed the speed rating that the driver is attempting to achieve.* Tires must be Bracket (Y) rated or a competition road race tire rated at speeds greater than 199 mph. **W-up to 168MPH, Y-up to 186MPH, [Y] "Bracket" (Y) 186MPH+**

Example: 315-35-R18 (Y)

- 6.1.1 Tires of any construction for use in land speed competition on nonpaved surfaces, tires designated for use in drag racing and biased ply tires designed for highway or off-road use, are strictly forbidden.
- 6.1.2 All tires must have a Temperature rating of "A" (or greater) and Speed Rating Bracket (Y). Load ratings below OEM requirements will not be allowed.

- 6.1.3** It is HIGHLY RECOMMENDED that the participant uses tires with a speed, temperature and load rating exceeding the rules set forth in this section.
- 6.1.4** Any Slick tire (non DOT stamped) must be approved by Chief of Tech at least 30 days prior to the event. Drag racing slicks are NOT allowed.
- 6.1.5** **Road Race** compounds carrying a speed rating of “W” may be run in excess of its stated speed rating at The Texas Mile and US Mile events.
- 6.1.6** Tires with a date code 7 years or older will not be allowed.
- 6.2** **Drivers Seat:** Drivers Seat: Seats must meet current SFI/FIA Competition Seat safety requirements. **Factory seats are not allowed.**
- 6.3** **FIRE EXTINGUISHER:** A 2 lb. minimum, automotive BC handheld fire extinguisher, with a secure quick release-mounting bracket preferably made of metal, mounted within easy reach of the Driver while normally seated, belts fastened, & steering wheel in place. **A fire system is recommended but not required.**
- 6.3** **HELMET:** Helmets must carry a SNELL SA-Rating (Special Application) **2015** or newer certification (**SA2015 or SA2020**). **Note: Helmets carrying only a DOT Certification as well as M-Rating (Motorcycle) helmets are forbidden for use in an automobile in any class at any speed. All helmets must be in sound condition including shell liner and strap.**
- 6.3.1** Helmets unable to display SNELL SA2015 or SA2020 stickers (located on the inner shell of the helmet) will not be approved for use.

6.3.2 Helmets must be full faced and have the face shield installed.

6.4 SEAT BELTS/SAFETY HARNESS/RESTRAINTS/HANS: All vehicles must have a five-, six-, or seven-point seat belt system/safety harness. **Proper submarine strap installation is required securing the strap bolt or bolts in line with the lap belt line bolts.** Arm restraints are required in all vehicles. **The use of a HANS device is required.**

6.4.1 All belts should meet at least one of the following:

A. SFI Specification 16.1 or 16.5 and shall bear a dated label of no more than five (5) years old. At least one date label is required on belt sets.

B. A restraint system meeting FIA spec #8853/1985, 8853/98, or D-###.T/98, including amendment 1/92 may be used. FIA certified belts have a label that shows an expiration date. The belts cannot be used past December 31st of the year shown on the label. At least one date label is required on belt sets. Belts cannot be over 5 years old by the date shown on the label.

6.4.2 A five-point system consists of: a three (3) inch lap belt, two shoulder belts that are either two (2) inch (*for use with HANS*), and a two (2) inch anti-submarine strap.

6.4.3 A six-point system is recommended for cars where the driver is seated in an upright (to thirty (30) degrees) or a semi-reclining position. It consists of two (2) anti-submarine belts in addition to lap and shoulder belts. Note: Current FIA-approved belt sets with two (2) inch lap belts are acceptable with the six-point system.

- 6.4.4** A seven-point system is recommended for seats with more than thirty (30) degrees of incline. Note: Current FIA Approved belt sets with two (2) inch lap belts are acceptable with the seven (7) point system.
- 6.4.5** The material of all straps should be nylon or polyester, and in new or perfect condition. The buckles should be metal quick release. There should be a common release for all belts.
- 6.4.6** All mounting hardware should be SAE grade five (5) or better. Large diameter mounting washers should be used to spread the load. Bolting through floor panels etc. is not acceptable without required washers. Please consult an experienced race car preparation shop for mounting your safety harness.
- 6.4.7** The seat shall meet current SFI/SFA requirements.
- 6.4.8** Only separate shoulder straps are permitted. "H" type belts are allowed. "Y" type belts are not allowed. Each shoulder strap must have an independent mounting point.
- 6.4.9** All drivers should take care to ensure that their belts are properly worn, adjusted, and latched. "Cam-lock" type belts can be subject to inadvertent release, should the driver fail to ensure that they are properly latched.
- 6.4.10** Any driver involved in a high impact crash shall send all of their safety belts back to the manufacturer for inspection, re-webbing if necessary, and re-certification before they may be used again. Proof of re-certification is the driver's responsibility.
- 6.5 CLOTHING:** An SFI 3.2A/1 (or better) Driver's suit and SFI 3.3 Driver's Accessories (gloves, shoes, underwear, socks, and balaclava (if you have facial hair) are required.

6.6 ROLL CAGE: All cars that are attempting speeds at or over 215 mph but below 230 mph are required to have a **NHRA 8.50 suitable type roll cage at minimum meeting the rules for your car build.**

6.6.1 Bar stock material minimums are as follows:

FOR DOM: under 2500lbs: 1.50"x 0.095"
 2501-3000lbs: 1.50"x 0.120" or 1.75" x 0.095"
 3001+lbs: 1.75"x 0.120"

FOR Alloy (CM) under 1500lbs: 1.375"x 0.095"
 1501-2500lbs: 1.50"x 0.095"
 2501-3000lbs: 1.50"x 0.120" or 1.75" x 0.095"
 3001+lbs: 1.75" x 0.120"

6.6.2 Construction: The roll cage must be welded at all unions and attachment points. Bolt in roll cages are not allowed. Stand-alone S bends within any section of tubing are not allowed.

6.6.3 All roll cage surfaces that may come in contact with the driver should be padded with high-density padding such as Ethafoam or Ensolite. It is recommended that padding meeting SFI specification 45.1 be used.

Any individual wishing to enter a vehicle which deviates from the rules listed above must contact the chief of tech 30 days prior to the event for approval.

6.7 BRAKES: All vehicles must have working front and rear brakes.

6.8 VEHICLE COMPONENTS IN GOOD OPERATING CONDITION: Please make sure your vehicle is in good working condition. No leaks from the vehicle or loose items within the vehicle are allowed. Floor mats need to be removed. Ice may be used for intercoolers. Fresh fluids such as lubricants and coolants throughout the vehicle are recommended. See the tech sheet for further details.

7.0 Automobile - Required Safety Equipment 230+ MPH

Prior safety and technical approval from other racing or land speed events is not proof or waiver allowing exemption from any automobile or driver safety specification set forth in these rules. The following safety equipment is required to be used for all automobiles running at 230+ mph and highly recommended for all other vehicles participating at the Texas/US Mile events. You must submit a safety equipment check-list to the Texas Mile or the U.S. Mile and gain approval to enter a vehicle attempting speeds over 199 mph. All Monocoque Chassis are given a 10 MPH additional safety bump at all speed requirements

ATTENTION: DOT TIRES MUST HAVE AN "A" TEMPERATURE RATING OR BETTER.

7.1 TIRES: TIRES MUST HAVE A TEMPERATURE RATING OF "A" OR BETTER. DOT-approved or competition road race tires in good condition are required to be used. *The tire speed rating must exceed the speed rating that the driver is attempting to achieve.* **Tires must**

be Bracket (Y) rated or a competition road race tire rated at speeds greater than 199 mph.

7.1.1 Tires of any construction for use in land speed competition on non-paved surfaces, tires designated for use in drag racing and biased ply tires designed for highway or off-road use, are strictly forbidden.

7.1.2 All tires must have a Temperature rating of “A” (or greater) and Speed Rating (Y). Load ratings below OEM requirements will not be allowed.

7.1.3 It is HIGHLY RECOMMENDED that the participant makes use of tires with a speed, temperature and load rating exceeding the rules set forth in this section.

7.1.4 Any Slick tire (non DOT stamped) must be approved by Chief of Tech at least 30 days prior to the event. Drag racing slicks are NOT allowed.

7.1.5 Hoosier R7 compounds carrying a speed rating of “W” may be run in excess of its stated speed rating at The Texas Mile and US Mile events.

7.1.6 Tires with a date code 7 years or older will not be allowed.

7.2 Drivers Seat: Seats must meet current SFI safety requirements for full containment seats. Factory seats are not allowed. The driver’s seat should be similar to the SFI 39.2 specifications.

7.3 FIRE EXTINGUISHER: A 2 lb. minimum, automotive BC handheld fire extinguisher, with a secure quick release-mounting bracket preferably made of metal, mounted within easy reach of the Driver while normally seated, belts fastened, & steering wheel in place is required. **A fire system is recommended but not required.**

7.4 HELMET: Helmets must carry a SNELL SA-Rating (Special Application) **2015** or newer certification (**SA2015 or SA2020**). **Note: Helmets carrying only a DOT Certification as well as M-Rating (Motorcycle) helmets are forbidden for use in an automobile in any class at any speed. All helmets must be in sound condition including shell liner and strap.**

7.4.1 Helmets unable to display SNELL SA2015 or SA2020 stickers (located on the inner shell of the helmet) will not be approved for use.

7.4.2 Helmets must be full faced and have the face shield installed.

7.5 SEAT BELTS/SAFETY HARNESS/RESTRAINTS/HANS: **The use of a HANS device is required.** All vehicles must have a five, six, or seven-point seat belt system/safety harness. Proper submarine strap installation is required. *Arm restraints are required in all vehicles.*

7.5.1 All belts should meet at least one of the following:

A. SFI Specification 16.1 or 16.5 and shall bear a dated label of no more than five (5) years old. At least one date label is required on belt sets.

B. A restraint system meeting FIA spec #8853/1985, 8853/98, or D-###.T/98, including amendment 1/92 may be used. FIA certified belts have a label that shows an expiration date. The belts cannot be used past December 31st of the year shown on the label. At least one date label is required on belt sets. Belts cannot be over 5 years old by the date shown on the label.

- 7.5.2** A five-point system consists of: a three (3) inch lap belt, two shoulder belts that are either two (2) inch (*for use with HANS*), and a two (2) inch anti-submarine strap. **Proper submarine strap installation is required securing the strap bolt or bolts in line with the lap belt line bolts**
- 7.5.3** A six-point system is recommended for cars where the driver is seated in an upright (to thirty (30) degrees) or a semi-reclining position. It consists of two (2) anti-submarine belts in addition to lap and shoulder belts. Note: Current FIA-approved belt sets with two (2) inch lap belts are acceptable with the six-point system.
- 7.5.4** A seven-point system is recommended for seats with more than thirty (30) degrees of incline. Note: Current FIA Approved belt sets with two (2) inch lap belts are acceptable with the seven (7) point system.
- 7.5.5** The material of all straps should be nylon or polyester, and in new or perfect condition. The buckles should be metal quick release. There should be a common release for all belts.
- 7.5.6** All mounting hardware should be SAE grade five (5) or better. Large diameter mounting washers should be used to spread the load. Bolting through floor panels etc. is not acceptable without required washers. Please consult an experienced race car preparation shop for mounting your safety harness.
- 7.5.7** Only separate shoulder straps are permitted. "H" type belts are allowed. "Y" type belts are not allowed. Each shoulder strap must have an independent mounting point.
- 7.5.8** All drivers should take care to ensure that their belts are properly worn, adjusted, and latched. "Cam-lock" type belts can be subject to inadvertent release, should the driver fail to ensure that they are properly latched.

7.5.9 Any driver involved in a high impact crash shall send all of their safety belts back to the manufacturer for inspection, re-webbing if necessary, and re-certification before they may be used again. Proof of re-certification is the driver's responsibility.

7.6 CLOTHING: An SFI 3.2A/1 (or better) Driver's suit and SFI 3.3 Driver's Accessories (gloves, shoes, underwear, socks, and balaclava (if you have facial hair) are required.

7.7 ROLL CAGE: All cars that are attempting speeds at or over 230 mph are required to have a **NHRA 25.3** roll cage at minimum.

7.7.1 Bar stock material required minimums are as follows:

FOR DOM: under 2500lbs: 1.50"x 0.095"
 2501-3000lbs: 1.50"x 0.120" or 1.75" x 0.095"
 3001+lbs: 1.75"x 0.120"

FOR Alloy (CM) under 1500lbs: 1.375"x 0.095"
 1501-2500lbs: 1.50"x 0.095"
 2501-3000lbs: 1.50"x 0.120" or 1.75" x 0.095"
 3001+lbs: 1.75" x 0.120"

7.7.2 Construction: The roll cage must be welded at all unions and attachment points. Bolt in roll cages are not allowed. All cages must have a halo bar as an integral part

of the welded in crash protection system (roll cage). Stand-alone S bends with in any section of tubing are not allowed.

7.7.3 All roll cage surfaces that may come in contact with the driver should be padded with high-density padding such as Ethafoam or Ensolite. It is recommended that padding meeting SFI specification 45.1 be used.

Any individual wishing to enter a vehicle which deviates from the rules listed above must contact the chief of tech 30 days prior to the event for approval.

7.8 BRAKES: All vehicles must have working front and rear brakes.

7.9 VEHICLE COMPONENTS IN GOOD OPERATING CONDITION: Please make sure your vehicle is in good working condition. No leaks from the vehicle or loose items within the vehicle are allowed. Floor mats need to be removed. Ice may be used for intercoolers. Fresh fluids such as lubricants and coolants throughout the vehicle are recommended. See the tech sheet for further details.

8.0 Automobile- Classification Rules

Class types for Automobiles

8.1 STREET LEGAL

8.2 NOT STREET LEGAL

8.3 EXHIBITION VEHICLE

8.4 After you choose your Automobile class you will be requested to answer ALL of the following questions:

8.4.1 Body Style- What is the body style of your automobile?

- 8.4.2 Speed Range-** Will your automobile go over 199 mph or stay below 199 mph?
- 8.4.3 Engine Induction-** Is your automobile naturally aspirated, turbo charged or supercharged?
- 8.4.4 Engine-**How many cylinders does your automobile have?
- 8.4.5 Cubic Inch / Liter Equiv. Range-** What is the engine displacement?
- 8.4.6 Fuel-** What type of fuel does your automobile run on?
- 8.4.7 Nitrous-** Does your automobile have nitrous?
- 8.4.8 Methanol Injected-** Is your automobile methanol injected?
- 8.4.9 Drive Line-** what is the driveline of your automobile?

**** By classifying your automobile as street legal or not street legal and answering the questions above you will be able to compare yourself to your peers running similar setups or configurations. This will allow for you to challenge yourself in more than one way.**

9.0 Motorcycles – Required Safety Equipment

The following safety equipment is required to be used for all motorcycles. The motorcycle safety tech rules are listed below. Riders are responsible for reading and complying with all these requirements.

9.1 ENGINE KILL SWITCH: Riders must have a lanyard style kill switch that kills all power in the event of a rider falling off.

9.2 TIRES: Tires must be rated for the top speed of your motorcycle.

9.3 SAFETY-WIRED ITEMS: The following items must be safety wired:

9.3.1 Front axel pinch bolts and rear axle nuts must be safety wired. If you are unable to safety wire you must contact a member of tech prior to the event. Factory rear axle nut cotter pins are acceptable.

9.3.2 Oil drain plugs must be safety wired and it is encouraged to safety wire the filler cap but is not required.

9.3.3 Drive chains must have the master link clip safety wired or silicone applied.

9.4 BREATHER HOSES: Crankcase breather hoses must be run into a catch tank or in to the air box.

9.5 CLOTHING: Leather racing suits must be worn. Suits may be one or two piece zip together. Kevlar T panels can only be used for expansion flexibility (arms and legs) and not to replace other large areas of leather. Leather gauntlet racing gloves are required. Boots suitable for motorcycle racing, must completely cover and surpass the ankle.

Driving shoes will not be permitted. Drag race or street low top boots are strictly prohibited. **Slip on boots are not allowed.**

9.6 HELMET: Helmets must carry a Snell M (Motorcycle) certification bearing **M2015** or M2020 or ECE R22-5. ECE helmets must be within 10 years of the listed date of manufacture. All Snell helmets must have at minimum M2010 dating. All helmets must be in sound condition, including shell, liner, and strap. All helmets must be approved by the tech inspector.

9.6.1 Helmets unable to display M2015 or M2020 or ECE date of manufacture will not pass tech.

9.6.2 Visor tear-offs are not allowed.

9.6.3 The Texas Mile and U.S. Mile prohibits hydration devices such as camel backs during competition events.

9.7 STEERING DAMPER: A steering damper is required for speeds greater than 140 mph.

9.8 BRAKES: Both front and rear brakes must be installed and functional.

** Anything not covered, but deemed unsafe by the tech inspector WILL NOT be permitted.

10.0 Motorcycles – Classification Rules

Class types for Motorcycles

10.1 **INLINE MOTOR /FACTORY STOCK**

10.2 **INLINE MOTOR /MODIFIED**

10.3 **INLINE MOTOR /UNLIMITED**

10.4 **V TWIN MOTOR / FACTORY STOCK**

10.5 **V TWIN MOTOR /MODIFIED**

10.6 **V TWIN MOTOR / UNLIMITED**

10.7 **EXHIBITION MOTORCYCLE CLASS**

10.8 **Read the following classification definitions to make sure you qualify for the class you chose.**

10.8.1 Factory Stock: Classification retains all a factory produced drive-train, electronics, chassis, exhaust, induction and layout. Modifications are allowed to meet the set safety requirements outlined in the technical rules and regulations. Cosmetic changes to the paint, ancillaries, and changes of tire make are allowed. Tires must retain a DOT rating. Performance enhancing modifications are not allowed to the drive-train, electronics, chassis, exhaust, induction and layout.

Factory Stock class will not allow any modification deemed speed enhancing by the Tech Inspection Official.

10.8.2 Modified: Classification allows the modification to the drive-train, chassis, exhaust, induction. Preparation is allowed e.g. the covering or removal of signal lenses, extensive safety wire, aftermarket plastics, etc. Drastic layout and chassis modification purposed for land speed racing will not be allowed in the Modified class.

The Tech Inspection Official retains the right to reclassify any Modified entrant not deemed street worthy. “Street worthy” generally specifies that the motorcycle is able to reasonably and safely; make over the road travel for an extended period of time starting and stopping and abide to local state safety inspection requirements. The motorcycle must be capable to perform the above without the aid of support vehicles or staff.

10.8.3 Unlimited: Classification allows an infinite amount of modifications to the bike specifically for the purpose of drag, road or land speed racing. Any participant may classify themselves as Unlimited. Chassis alteration, layout or engine modification is not required.

Any entrant has the right to move up in classification if he or she wishes. Moving up delineates that your bike runs a lesser engine displacement and/or classifies lower than the class the rider wishes to be moved up into. Entrants may not classify themselves into a lesser class unless specifically allowed by the Tech Inspection Official.

10.9 After you choose your Motorcycle class you will be requested to answer ALL of the following questions:

10.9.1 Body Style- What is the body style of your motorcycle?

10.9.2 Manufacture Origin- Where was your motorcycle made?

10.9.3 Engine Induction- Is your motorcycle naturally aspirated, turbo charged, or supercharged?

10.9.4 Engine- How many cylinders does your motorcycle have?

10.9.5 Cubic Centimeters- What is the engine displacement?

10.9.6 Fuel- What type of fuel does your motorcycle run on?

10.9.7 Nitrous- Does your motorcycle have nitrous?

10.9.8 Methanol Injected- Is your motorcycle methanol injected?

10.9.9 Inches over stock length- has the frame of your motorcycle been extended?

****By classifying your motorcycle and answering the questions above you will be able to compare yourself to your peers running similar setups or configurations. Now you can compare your bike with other bikes on many different levels, from a broad range to a very narrow range. This will allow for you to challenge yourself in more than one way.**

In order to be classified in the NEW American Iron Class you **MUST** choose the USA as the manufacture origin of your bike and you **MUST** choose Sport Bike or Classic as the body style of your motorcycle.

11.0 Land Speed Racer Classification

LSR Classification Types

11.1 LAND SPEED RACING AUTOMOBILE

11.2 LAND SPEED RACING MOTORCYCLE

**** The Texas Mile and U.S. Mile honors classes for Land Speed Racing. For more information refer to <http://www.landracing.com/>. Each LSR participant will need to populate their own class according to the SCTA rules.**

11.3 If you chose LSR Automobile you will be requested to answer ALL of the following questions:

11.3.1 Body Style- What is the body style of your Automobile?

11.3.2 Speed Range- Will your automobile go over 199 mph or stay below 199 mph?

11.3.3 Engine Induction- Is your automobile naturally aspirated, turbo charged or supercharged?

11.3.4 Engine-How many cylinders does your automobile have?

11.3.5 Cubic Inch / Liter Equiv. Range- What is the engine displacement?

11.3.6 Fuel- What type of fuel does your automobile run on?

11.3.7 Nitrous- Does your automobile have nitrous?

11.3.8 Methanol Injected- Is your automobile methanol injected?

11.3.9 Drive Line- what is the driveline of your automobile?

11.4 If you chose LSR Motorcycle you will be requested to answer ALL of the following questions:

11.4.1 Body Style- What is the body style of your motorcycle?

11.4.2 Manufacture Origin- Where was your motorcycle made?

11.4.3 Engine Induction- Is your motorcycle naturally aspirated, turbo charged, or supercharged?

11.4.5 Engine- How many cylinders does your motorcycle have?

11.4.6 Cubic Centimeters- What is the engine displacement?

11.4.7 Fuel- What type of fuel does your motorcycle run on?

11.4.8 Nitrous- Does your motorcycle have nitrous?

11.4.9 Methanol Injected- Is your motorcycle methanol injected?

11.4.10 Inches over stock length- has the frame of your motorcycle been extended?

11.5 Body Style Definitions for Motorcycles

11.5.1 Sport bike or Superbike is a motorcycle optimized for speed, acceleration, braking, and cornering on paved roads, typically at the expense of comfort in comparison to less specialized motorcycles. The riding position has the rider leaning over the fuel tank with their feet behind them.

11.5.2 Sport-Touring Bikes: blends performance with long-distance capabilities while providing comfort and relative safety to the rider. Generally, these bikes are still designed more for comfort than speed and performance. They fall between sport and touring.

11.5.3 Classic/Cruiser/Touring Motorcycles: These bikes are large and heavy motorcycles designed for comfort on long rides and not for speeds equal to sport bike. The riding position on these bikes are usually but not always places the feet forward and the hands up, with the spine erect or leaning back slightly.

11.5.4 Chopper/Bobber/Cafe/Brat/Scrambler: Whether you have a modified frame or not, this is the class for your custom motorcycle. This class is for all the bikes that are not mass produced. It's the place for truly one of a kind custom bikes.

11.5.5 Enduro/Dual-Sport Motorcycles: These bikes are designed for use both on-road and off-road use. These motorcycles cover a large spectrum from basically dirt bikes with headlights and turn signals to a more traditional road bike with a suspension designed to soak up the bumps off road use has to offer. Dual Sport motorcycles tend to be tall, with a high center of gravity.

11.5.6 Other: This is for all the bikes that don't fit nicely into one of the above classes. If you have something rare or unique or just not listed above then this is where you go.

Classification is ultimately up the discretion of the Tech Inspection Official. The Tech Inspection Official in accordance with the Race Director retain the right to reclassify any entrant at any time during the course of the event.

12.0 Competitor Licensing

Licenses and requirements are separate for automobiles and motorcycles. A license level in the motorcycle class doesn't apply to the car classes and vice versa.

The competitor will be issued a hard card license. The competitor must notify the Race Director or Chief of Tech when they wish to move up to Class A and/or AA license level. Failure to follow these polices can and will result in the competitor forfeiting all competition privileges for the event and possible future events. In the event that a competitor is found to be cheating by allowing another driver/rider to use their licensing band, they both will be permanently banned from all future Texas Mile and U.S. Mile events. The Race Directors decision is final in all matters pertaining to all event rules.

12.1 CLASS C – The minimum qualification for a Class C license is a valid US, Canadian provincial, military or any other approved driver's license. All other licenses must be approved prior to the event. It is the competitor's responsibility to have their licenses approved. Class C license holders are limited to **160 mph**.

12.2 CLASS B – The minimum qualification for a Class B license is a Class C license, plus sufficient acceptable prior experience or successful completion of one run with a trap speed greater than **140 mph** but less than **160 mph**. **Class B** license holders are limited to **199 mph**.

12.3 CLASS A – The minimum qualification for a Class A license is a Class B license, plus sufficient acceptable prior experience or successful completion of one run with a trap speed greater than **180 mph** but less than **200 mph**.

Automobiles - An approved race license from the following sanctioning bodies: ECTA, SCTA, NHRA, IHRA, NASCAR, ARCA, SCCA, NASA, Grand Am, IMSA, or FIA will be accepted for a Class A license. Class A license holders are limited to **220 mph**.

Motorcycles - An approved race license from the following sanctioning bodies: CMRA, ECTA, SCTA, NHRA, or IHRA, will be accepted for a Class A license. Class A license holders are limited to **220 mph**.

12.4 CLASS AA – (color TBD) Highest level license. The competitor must demonstrate to the satisfaction of the Race Director and/or the Chief of Tech that they are sufficiently qualified to run at the highest licensing level. Graduation to a Class AA license is not automatic and applicants must be individually approved by the Race Director and/or the Chief of Tech. Minimum qualifications are:

- a Class A license;
- considerable high speed driving experience or an approved race license from the following sanctioning bodies:

Automobiles - ECTA, SCTA, NHRA, IHRA, NASCAR, ARCA, SCCA, NASA, Grand Am, IMSA, or FIA;

Motorcycles - CMRA, ECTA, SCTA, NHRA, or IHRA, and,

- *Two or more* successful runs greater than 200 mph but less than **230** mph.

12.5 The Race Director has the final say in all licensing and cannot be protested to a higher level.

Contact Us

If you have any questions about the above rules, please contact our Chief of Tech.

Kevin Mixon, Chief of Tech, (832)658-1236, tech@texasmile.net

If you have questions regarding registration or general event info, please contact Ashley Flores.

Ashley Flores, Director of Operations, (281)303-1844, info@texasmile.net